12W Portable Solar Panel-Solar Charger Series

Tel:+86-755-8638 1663 Fax:+86-755-8638 1665 Cell:+86-18018791660 www.brightsolarpower.net
Address: 8th Floor, Building 1, Nanchang First Industrial Zone, Nanchang Community, Xixiang Street, Bao 'an District, Shenzhen, GuangDong, China.

Model	BS12-PSP-SC
Nominal peak power(WP):	12 W
Cell Type	Mono / Sunpower / HPBC LONGI Cell
Efficiency	22.5%-25.8%
Max Operating Voltage (Vmp)	5.00 V
Max Operating Current (lpm)	2.40 A
Open Circuit Voltage (Voc)	6.00 V
Short Circuit Current (Isc)	2.59 A
Unfolded Size(mm)	376*275*16mm
Folded Size(mm)	/
Color	Black/White
Construction	Standard ETFE / PET
	Anti-crack material
Power temperature coefficient	-0.24%/°C
Voltage temperature coefficient	-0.25%/°C
Current temperature coefficient	-0.06%/°C
NOCT	45±2°C
Tolerance	0~ +3%
Customized LOGO	LOGO on backing label
Certification	CE,ROHS,UKCA,ISO9001:2015
Package	1 unit per inner box, 5 inner boxes per master carton.