55W Flexible Solar Panel-L Series

Tel:+86-755-8638 1663 Fax:+86-755-8638 1665 Cell:+86-18018791660 www.brightsolarpower.net
Address: 8th Floor, Building 1, Nanchang First Industrial Zone, Nanchang Community, Xixiang Street, Bao 'an District, Shenzhen, GuangDong, China.

Model	BS55-FT-S(E)
Nominal peak power(WP):	55 W
Cell Type	166*166mm/Sunpower
Efficiency	22.5-25.8%
Vmp(V)	18.00 V
Ipm(A)	3.05 A
Voc(v)	22 V
Isc(A)	3.28 A
Product Size(mm)	575*535*3.1mm
Weight(KG)	1.1 KG
Color	Black/White
Construction	Standard ETFE
	Anti-crack material
Power temperature coefficient	-0.24%/°C
Voltage temperature coefficient	-0.25%/°C
Current temperature coefficient	-0.06%/°C
NOCT	45±2°C
Max system voltage:	300V DC
Tolerance	0~ +3%
Customized LOGO	LOGO on backing label
Accessories (option)	4.0m² 90cm (+),90cm (-) PV Cables + MC4 Connectors or Single 2-core 2*2.5m² Cable
Certification	CE,ROHS,IEC 61215,UKCA,ISO9001:2015
Package	1 unit per inner box, 5 inner boxes per master carton.